



NAME: HD5218UA

Product Description:

HD5218UA is high density polyethylene copolymer containing butene-1(C4) as comonomer. It is suitable for thin wall injection moulding applications.

HD5218UA has the following characteristics: high warpage resistance, high flow, fast cycling injection moulding, UV stabilized.

Applications:

General purpose injection moulding with outdoor indoor applications.

Typical data: (Table)

PROPERTY	UNIT	METHOD	VALUE
MELT FLOW INDEX(2.16KG)	g/10min	ASTM D-1238	18
DENSITY	gr/cm ³	ASTM D-1505	0.952
YELLOW INDEX	-	ASTM E-313	-1
WHITENESS INDEX	-	ASTM E-313	60
CONTAMINATION	NO.	BP137	5
VICAT SOFTENING POINT	°C	ASTM D-1525	115
TENSILE STRESS AT YEILD	MPA	ASTM D-638	20
ELONGATION AT BREAK	%	ASTM D-638	900
CHARPYIMPACT	KJ/M ²	ASTM D-6110	3

* All above mentioned data are typical values and not to be construed as real specifications. Users should confirm results by their own tests. For more information about guaranteed items, please refer to S.S.S. (Standard Sales Specifications)
Grade Suffix (Additives Indication):